

# HAND HELD

## Venus FUTURA

Three temperature settings (not FP POL). Maximum seal length 150mm. Optional Foot Pedal Kit with chain and clamps.



FP POL

FP CEL

POLY TW

BARRIER

Optional foot pedal kit.

**FP POL** For sealing light to medium polythene bags up to 2 x 150um thick. Single heated jaw makes 2mm wide seal.

**FP CEL** For sealing cellulose films, waxed papers and foil laminates up to 2 x 200um thick. Twin heated crimp seal jaws make a strong 10mm wide seal.

**POLY TW** For sealing medium to heavy gauge polythene bags up to 2 x 250um thick. Twin heated jaws make a

2mm wide seal.

**BARRIER** For sealing cellulose, foil or paper laminates up to 2 x 200um thick. Seal width 10mm.



## Venus SUPER POLY

For extra thick bags. The Venus Super Poly impulse sealers have an easy plier action. A separate transformer and a 3.5 metre lead allow complete portability for jobs that are too big to move about. Seals polythene, polypropylene and laminates up to 2 x 250um thick. Choose from 280, 380 and 630mm sealing lengths.

### SUPER CELLO

Super Cello 400, seal length 400mm.

Super Cello 300, seal length 300mm.

SUPER POLY 280

SUPER POLY 380

Constant heat, plier action sealers for jobs that are too big to move about. The 4.5 metre lead between transformer and sealer allows you to take Super Cello to the job. \*Seals cellulose, heavy film, laminates, coated foils and wax coated papers. \*Sealing lengths: 300mm and 420mm. \*Seal thickness: Up to 2 x 100 microns. \*Seal width: 10mm. \*Temperature adjustable from 60°C to 250°C.



The separate transformer is the key to the extremely lightweight plier action sealing jaws.

# WALL MOUNTED

## Venus PRONTO

Designed for confectioners, chemists and hardware stores, the Pronto's ingeniously designed jaw mechanism allows the bag to be held upright with both hands. Seals polythene and polypropylene up to 2 x 200um thick. Available in 255mm and 420mm seal lengths with timer and optional print seal.

PRONTO 420P WITH PRINT SEAL

PRONTO 255A WITH BENCH MOUNTING STAND (OPTIONAL)



USE BY  
Embossed print seal

## Venus SHOP SEALERS

Wall or bench mounted impulse sealer with seal time control and stainless steel casing. Seals bags in the upright position to prevent spillage. Suitable for sandwich bars, pharmacies, confectioners, hardware stores.

\*Seals polythene and polypropylene. \*Seal width: 2mm or 5mm. \*Seal thickness: up to 2 x 100 microns.



VHIS250, seal length 250mm, seal width 2mm. VHIS255, seal length 250mm, seal width 5mm.

VHV200, seal length 200mm, seal width 2mm and 3mm. VHV300, seal length 300mm, seal width 2mm and 3mm.



# HEAVY DUTY

ULTIMATE HSP 600

AUTOMASTER AM 600

## Venus ULTIMATE and AUTOMASTER

The Ultimate is used in hospitals for an airtight seal on sterilisation bags (Autoclave paperfilm). It also seals polythene, polypropylene and some PVC and polyamide films. Internal air compressor to operate high pressure twin heated jaws. Also features electronic timer, cool-down cycle, cutter, safety guard, and electronic foot switch operation. Similar in design, but with single element, the Automaster seals polythene, polypropylene and laminated foils. Both are excellent performers in harsh environments where dust, moisture, powder coatings etc can cause problems. They produce a strong 5mm wide seal using material up to 2 x 250um thick.



# AUTOMATIC

## Venus VHVD Venus VHIFT

### ORIGINAL VHIFT

A heavy duty impulse sealer for polythene and polypropylene bags up to 2 x 300um thick. Automatic or electronic foot switch operation with timer and cool-down cycle.

Model options. 2mm wide seal: VHIFT 452 and VHIFT 602. 5mm wide seal: VHIFT 455 and VHIFT 605.



VHIFT 602

### Venus VHIFT III

A stronger wider seal on thicker bags. Extra power and model options allow you to create a 2mm, 5mm or 10mm wide seal on polythene and polypropylene bags up to 2 x 500um thick.

The extra power and wider element wire handle the most difficult sealing jobs, even where powders or liquids line the bags. Bench mounted with automatic electronic foot switch operation, timer, and cool-down cycle.

Model Options. 2mm wide seal: VHIFT III 302, VHIFT III 452 and VHIFT III 602. 5mm wide seal: VHIFT III 305, VHIFT III 455 and VHIFT III 605. 10mm wide seal: VHIFT III 309 and VHIFT III 459. 10mm wide double seal: VHIFTD 309, VHIFTD 459, VHIFTD 609.



VHIFT III 455